(11)Publication number:

2000-087217

(43)Date of publication of application: 28.03.2000

(51)Int.CI.

C23C 14/06

(21)Application number: 10-254025

(22)Date of filing:

08.09.1998

(71)Applicant: KOBE STEEL LTD

(72)Inventor: YASUNAGA TATSUYA


YAMAMOTO KENJI **URUSHIBARA WATARU**

KATO ATSUSHI SATO TOSHIKI

(54) TITANIUM NITRIDE COATED SLIDING MEMBER EXCELLENT IN WEAR RESISTANCE

PROBLEM TO BE SOLVED: To provide a TiN coated sliding member in which the surface of a base material having 300 to 800 Hv hardness is provided with a TiN coating layer, and chipping hardly occurs and having sufficient wear resistance even in high facial pressure sliding conditions.

SOLUTION: The hardness of a base material is 300 to 800 Hv, and, moreover, the difference between the dynamic hardness HD and plastic deformation hardness Hp on the surface of a TiN coating layer measured by continuously loading triangular pyramid indenters of diamond from a load 0 to 5 gf and moreover continuously removing the loads from load 5 to 0 gf is 800 to 1500 kgf/mm2. Furthermore, the sound wave generating lowest load La in scratch testing is ≥30 N and moreover, the difference between the load Lc at which the magnitude of the rupture of the TiN coating layer reaches 10 µm diameter and the La is ≥50 N.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C): 1998,2003 Japan Patent Office

4. O Elicabilla Mall EV 633 051 786 US 600 12 2005